

VALUE WRAP



THE BEST PRICE-TO-PERFORMANCE VALUE ON THE MARKET

Get the quality and features you want from a GreenGuard® housewrap at exceptional savings with our hard-working Value Wrap.

Air and Moisture Protection Value Wrap adds a layer of air and moisture resistance to your structures, while breathing to allow moisture vapor to escape.

Tough and Reliable Value Wrap is designed not to tear, which means less waste on the job site. It also stands up to harsh sunlight remarkably well, staying UV-stable for up to 12 months.

Simple Installation With its translucent design, Value Wrap makes it easy to find studs, edges, corners, and openings for quick installation. The wrap is also lightweight, so it's easy to work with.

Custom Printing We can print your company name and logo on Value Wrap to create an on-site advertisement. See your sales representative or green-guard.com for additional information.



SIZES AVAILABLE

	4½' x 195' Roll	9' x 100' Roll	9' x 150' Roll	9' x 195' Roll
Value Wrap	●	●	●	●



VALUE WRAP

TYPICAL PHYSICAL PROPERTIES

Property	Test Method	Value Wrap
Nominal Thickness ¹ (inches) (mils)	ASTM D 1777	.008 8
Weight (lbs./1,000 ft. ²)	ASTM D 3776	13.0
Tensile Strength (lbs./in., MD/TD) ²	ASTM D 882	45/29
Trapezoid Tearing Strength (lbs./in., MD/TD) ²	ASTM D 1117	32/41
Burst Strength (psi)	ASTM D 751	111
Water Resistance (minutes)	ASTM D 779	36
Water Vapor Permeance (perm)	ASTM E 96 Procedure A (75°F, 50% R.H.)	15
Water Vapor Transmission Rate (g/m ² /24 hrs.)	ASTM E 96 Procedure A (75°F, 50% R.H.)	105
Fire Characteristics ³ Flame Spread Smoke Developed	ASTM E 84	0 25
Air Leakage Rate/Air Resistance (cfm/ft ² @ 75 Pa/25 mph)	ASTM E 283	0.03
Structural Integrity (minimum 1 hr. @ 500 Pa/65 mph)	ASTM E 330 Procedure A	Pass
Water Resistance (15 min. @ 27 Pa/15 mph)	ASTM E 331	Pass

DIMENSIONS/PACKAGING

Roll Size	4 1/2' x 195'	9' x 100'	9' x 150'	9' x 195'
Square Feet/Roll	877	900	1,350	1,755
Roll Weight (lbs.)	13	13	20	25
Rolls/Pallet	32	60	40	32
Pallet Size	42" x 54"	42" x 109"	42" x 109"	42" x 109"
Pallets/Truck	40	20	20	20

Compliance – Value Wrap complies with all relevant building codes. For the most current compliance information, go to green-guard.com.

GreenGuard® Disclaimers and Footnotes

- **WARNING:** Housewrap will ignite if exposed to fire of sufficient heat and intensity. Protect housewrap from exposure to open flame or other ignition sources during shipping, storage, and installation.
- Moisture Management of GreenGuard Housewraps: GreenGuard housewraps are excellent secondary weather barriers that help deflect water and wind-driven rain, yet are designed to breathe to assist trapped moisture vapor to escape, helping walls dry faster. GreenGuard housewraps are made of synthetic materials that are generally recognized as not providing a food source for insects, fungus, mold, or mildew. GreenGuard housewraps should always be properly installed and stored.
- Pactiv Building Products believes the information and recommendations herein to be accurate and reliable. However, since use conditions are not within its control, Pactiv Building Products does not guarantee results from use of such products or other information herein and disclaims all liability from any resulting damage or loss. NO WARRANTY, EXPRESS OR IMPLIED, IS GIVEN AS TO THE MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR OTHERWISE WITH RESPECT TO THE PRODUCTS REFERRED TO.
- For more information on specific building product recommendations and installation guidelines, contact your Pactiv Building Products insulation representative.

¹Low Point (.010 inches/10 mils), High Point (.020 inches/20 mils).

²Machine Direction/Cross Direction.

³These numerical flame spread and smoke ratings are not intended to reflect hazards presented by this material under actual fire conditions.

GreenGuard is a registered trademark of Pactiv Building Products.

© 2005 Pactiv Building Products, 3/05.

PS-HVWV

When correctly installed, Pactiv's Value Wrap can help reduce air leaks as is recommended by EPA's ENERGY STAR Home Sealing Effort.

	ENERGY STAR HOME SEALING
	<p>EPA recommends sealing air leaks that surround your living space:</p> <ul style="list-style-type: none"> • Attic sealing • Baseboards • Windows • Doors <p>ENERGY STAR is a program of the U.S. Environmental Protection Agency and the U.S. Department of Energy.</p> <p>www.energystar.gov</p>

